

Model 701-S



HP/KW	7.5/5.6
SWEEP OF DISCS	27" (685,8 mm)
ABRASIVE PRESSURE	440 LBS (200 kg)
WIDTH OF MACHINE	27-1/4" (692 mm)
LENGTH OF MACHINE HANDLE UP	29-1/4" (743 mm)
LENGTH OF MACHINE HANDLE DOWN	56-1/2" (1435 mm)
HEIGHT OF MACHINE	37-1/2" (952,5 mm)
NET WEIGHT	800 lbs (363 kg)
SHIPPING WEIGHT	860 lbs (390 kg)
WATER TANK	7 gallon (26,5 L)
POWER CORD (8-3)	100 ft (30,5 m)

ELECTRICAL OPTIONS

VOLTAGE	230	230	230	230	460
PHASE	1	1	3	3	3
DRIVE	MANUAL	VARIABLE	MANUAL	VARIABLE	VARIABLE
AMP DRAW	34	34	22	22	11
BREAKER (AMPS)	50	50	30	30	30
STONE HOLDER RPM	390	390-585	390	390-585	390-585

* WEIGHT MEASURED WITH FOUR POCKET WEIGHTS

- Optimal for jobs under 5,000 sq. ft.
- Mild Steel or Stainless Steel Guards
- Stainless Steel Water Tanks
- Wet/Dry Setup
- Direct Drive, No Belts
- Leveling System
- Adjustable Handle
- Uses Plug Stone Shape, Bolt on to Universal Tool Plate, or Speed Shift System

PRODUCTION RATES

- Mastic removal rate of 350 sq. ft. per hour
- Thin-Set removal rates of 400 sq. ft. per hour
- Thin-Mil coatings removal of 200 sq. ft. per hour
- Concrete polishing rates of 450 sq. ft. per polishing pad per hour (depending on grit)
- Rough Terrazzo rate of 600 sq. ft. per day



222 1st Avenue NW • Watertown, SD 57201
 Phone: (605) 882-3888 • Fax: (605) 882-0778
 Email: info@terrco.com • Website: www.terrco.com

